

Philips 6000 series 27B2U6903/00 Monitor PC 68,6 cm (27") 3840 x 2160 Pixel 4K Ultra HD LED Antracite

Marchio : Philips

Famiglia del prodotto: 6000 series

Codice prodotto: 27B2U6903/00

Nome del prodotto : 27B2U6903/00

Business Monitor 27B2U6903 Monitor 4K UHD con Thunderbolt™ 4

Philips 6000 series 27B2U6903/00 Monitor PC 68,6 cm (27") 3840 x 2160 Pixel 4K Ultra HD LED Antracite:

Questo monitor presenta una connettività super veloce. Grazie alla combinazione della porta Thunderbolt 4, la funzione Smart KVM e risoluzione 4K UHD, offre erogazione di potenza, commutazione della sorgente e immagini straordinarie in un unico monitor.  
Philips 6000 series 27B2U6903/00. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 3840 x 2160 Pixel, Tipologia HD: 4K Ultra HD, Tecnologia display: LED, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Hub USB integrato, Versione dell'hub USB: 3.2 Gen 2 (3.1 Gen 2). Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Antracite



| Display                        |                      | Ports & interfaces                |   |
|--------------------------------|----------------------|-----------------------------------|---|
| Display diagonal *             | 68.6 cm (27")        | Thunderbolt 4 ports quantity      | 2   |
| Display resolution *           | 3840 x 2160 pixels   | Headphone out *                   | ✓   |
| HD type *                      | 4K Ultra HD          | Microphone in                     | ✓   |
| Native aspect ratio *          | 16:9                 | HDCP                              | ✓   |
| Display technology *           | LED                  | HDCP version                      | 1.4/2.2   |
| Panel type *                   | IPS                  | Network                           |   |
| LED backlight                  | ✓                    | Ethernet LAN                      | ✓   |
| Backlight type                 | RGB LED              | Ergonomics                        |   |
| Touchscreen *                  | ✗                    | VESA mounting *                   | ✓   |
| Display brightness (typical)   | 350 cd/m²            | Panel mounting interface          | 100 x 100 mm  |
| Response time *                | 4 ms                 | Cable lock slot *                 | ✓   |
| Response time measurement type | GTG (Gray to Gray)   | Cable lock slot type              | Kensington  |
| Anti-glare screen              | ✓                    | Height adjustment *               | ✓   |
| Screen shape *                 | Flat                 | Adjustable height (max)           | 15 cm   |
| Contrast ratio (typical) *     | 1000:1               | Swivelling                        | ✓   |
| Contrast ratio (dynamic)       | 50000000:1           | Swivel angle range                | -180 - 180°   |
| Maximum refresh rate *         | 60 Hz                | Tilt adjustment                   | ✓   |
| Viewing angle, horizontal      | 178°                 | Tilt angle range                  | -5 - 30°  |
| Viewing angle, vertical        | 178°                 | Picture-in-Picture                | ✓   |
| Display number of colours *    | 1.07 billion colours | On Screen Display (OSD)           | ✓   |
| Pixel density                  | 163 ppi              | On Screen Display (OSD) languages | Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian |
| Viewable size, horizontal      | 59.7 cm              |                                   |   |
| Viewable size, vertical        | 33.6 cm              | Number of OSD languages           | 21  |
| Digital horizontal frequency   | 30 - 140 kHz         | Plug and Play                     | ✓   |
| Digital vertical frequency     | 23 - 75 Hz           |                                   |   |
| Display diagonal (metric)      | 68.5 cm              |                                   |   |
| DDC/CI                         | ✓                    |                                   |   |
| Haze rate                      | 25%                  |                                   |   |

| Display                               |                                    | Ergonomics                        |   |
|---------------------------------------|------------------------------------|-----------------------------------|---|
| Surface hardness                      | 3H                                 | LED indicators                    | Operation, Stand-by   |
| Performance                           |                                    | Power                             |   |
| VESA Adaptive Sync support            | ✓                                  | Energy efficiency class (SDR) *   | E   |
| Component video sync                  | Separate sync, Sync-on-green (SOG) | Power consumption (typical) *     | 28.6 W  |
| Flicker-free technology               | ✓                                  | Power consumption (standby) *     | 0.45 W  |
| Low Blue Light technology             | ✓                                  | Power consumption (off)           | 0.4 W   |
| Multimedia                            |                                    | AC input voltage                  | 100 - 240 V   |
| Number of speakers                    | 2                                  | AC input frequency                | 50/60 Hz  |
| RMS rated power                       | 6 W                                | Power supply type                 | Internal  |
| Built-in speaker(s) *                 | ✓                                  | Operational conditions            |   |
| Built-in camera *                     | ✗                                  | Operating temperature (T-T)       | 0 - 40 °C   |
| Design                                |                                    | Storage temperature (T-T)         | -20 - 60 °C   |
| Market positioning *                  | Office                             | Operating relative humidity (H-H) | 20 - 80%  |
| Product colour *                      | Anthracite                         | Storage relative humidity (H-H)   | 20 - 80%  |
| Feet colour                           | Charcoal                           | Operating altitude                | 0 - 3658 m  |
| Ports & interfaces                    |                                    | Non-operating altitude            | 0 - 12192 m   |
| Built-in USB hub *                    | ✓                                  | Weight & dimensions               |   |
| USB hub version                       | 3.2 Gen 2 (3.1 Gen 2)              | Width (with stand)                | 613 mm  |
| USB upstream port type                | USB Type-C                         | Depth (with stand)                | 230 mm  |
| Number of upstream ports              | 2                                  | Height (with stand)               | 544 mm  |
| USB Type-A downstream ports quantity  | 4                                  | Weight (with stand)               | 7.15 kg   |
| USB Type-C downstream ports quantity  | 2                                  | Width (without stand)             | 613 mm  |
| USB Type-C DisplayPort Alternate Mode | ✓                                  | Depth (without stand)             | 59 mm   |
| USB Power Delivery (USB PD)           | ✓                                  | Height (without stand)            | 371 mm  |
| USB Power Delivery up to              | 100 W                              | Weight (without stand)            | 5.1 kg  |
| HDMI *                                | ✓                                  | Packaging data                    |   |
| HDMI ports quantity                   | 2                                  | Package width                     | 780 mm  |
| HDMI version                          | 2.0                                | Package depth                     | 161 mm  |
| DisplayPorts quantity                 | 1                                  | Package height                    | 480 mm  |
| DisplayPort version                   | 1.4                                | Package weight                    | 10.2 kg   |
|                                       |                                    | Packaging content                 |   |
|                                       |                                    | Stand included                    | ✓   |
|                                       |                                    | Cables included                   | AC, DisplayPort, HDMI, Thunderbolt  |
|                                       |                                    | Manual                            | ✓   |
|                                       |                                    | Other features                    |   |
|                                       |                                    | Compliance certificates           | CB, CE, EAC, Federal Communications Commission (FCC), GS mark, ICES, RoHS, TÜV mark, UKCA |



8712581804749

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAR-2025. Prints or copies of Information are only valid on the printed Publication date