



LG 75XF3C-B Pannello piatto per segnaletica digitale 190,5 cm (75") LED Wi-Fi 3000 cd/m² 4K Ultra HD Nero Processore integrato WebOS

Marchio : LG

Codice prodotto: 75XF3C-B.AEU

Nome del prodotto : 75XF3C-B



LG 75XF3C-B. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 190,5 cm (75"), Tecnologia display: LED, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 3000 cd/m², Tipologia HD: 4K Ultra HD. Wi-Fi. Sistema operativo incluso: WebOS. Colore del prodotto: Nero



Display		Design	
Display diagonal *	190.5 cm (75")	Bezel width (bottom)	1.18 cm
Display technology *	LED	Bezel width (side)	1.18 cm
Display resolution *	3840 x 2160 pixels	Bezel width (top)	1.18 cm
Display brightness *	3000 cd/m ²	Performance	
HD type *	4K Ultra HD	Purpose *	Universal
Touchscreen *	✗	Smart modes	Energy saving
Native aspect ratio	16:9	Power	
Response time	8 ms	Power consumption (typical) *	660 W
Viewing angle, horizontal	178°	Power consumption (standby) *	320 W
Viewing angle, vertical	178°	Energy efficiency class (SDR)	A
Display diagonal (metric)	189 cm	Energy efficiency class (HDR)	A
Ports & interfaces		AC input voltage	100 - 240 V
HDMI ports quantity *	2	AC input frequency	50 - 60 Hz
HDMI input ports quantity	2	Computer system	
DVI port *	✓	Computer system *	✓
DVI-D ports quantity	1	Built-in processor *	✓
DisplayPorts quantity *	2	Operating system installed	WebOS
DisplayPorts in	1	Weight & dimensions	
DisplayPorts out	1	Display width	1675.2 mm
USB port *	✓	Display depth	123.9 mm
Ethernet LAN *	✓	Display height	953.6 mm
Ethernet LAN (RJ-45) ports	1	Display weight	36.7 kg
Wi-Fi *	✓	Packaging data	
Audio (L/R) in	1	Package width	1816 mm
Audio (L/R) out	1	Package depth	285 mm
RS-232 interface	✓	Package height	1106 mm
RS-232C	✓	Package weight	46.3 kg
Remote (IR) input	1	Packaging content	
Card reader integrated	✓	Remote control included	✓
Compatible memory cards	SD	Cables included	AC, DVI, DisplayPort, HDMI, IR sensor
Audio			
Built-in speaker(s) *	✗		

Design		Operational conditions	
Product design *	Digital signage flat panel	Operating temperature (T-T)	0 - 50 °C
Placement supported *	Indoor/outdoor	Operating relative humidity (H-H)	10 - 85%
Orientation	Horizontal/Vertical		
Product colour *	Black		
VESA mounting *	✓	Harmonized System (HS) code	85285210

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.