



## LG 75UL3J-E Pannello piatto per segnaletica digitale 190,5 cm (75") IPS Wi-Fi 330 cd/m² 4K Ultra HD Blu WebOS 16/7

Marchio : LG

Codice prodotto: 75UL3J-E.AEU

Nome del prodotto : 75UL3J-E

LG 75UL3J-E. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 190,5 cm (75"), Tecnologia display: IPS, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 330 cd/m², Tipologia HD: 4K Ultra HD. Wi-Fi. Ore di servizio (ore/giorni): 16/7. Sistema operativo incluso: WebOS. Colore del prodotto: Blu



Display		Performance	
Display diagonal *	190.5 cm (75")	Operating hours (hours/days)	16/7
Display technology *	IPS	HDCP	✓
Display resolution *	3840 x 2160 pixels	Smart modes	Energy saving
Display brightness *	330 cd/m²	HDCP version	2.2
HD type *	4K Ultra HD	<b>Power</b>	
Touchscreen *	✗	Power consumption (typical) *	155 W
Response time	8 ms	Power consumption (off)	0.5 W
Contrast ratio (typical)	1200:1	AC input voltage	100 - 240 V
Contrast ratio (dynamic)	1000000:1	AC input frequency	50 - 60 Hz
Viewing angle, horizontal	178°	Heat dissipation	529 BTU/h
Viewing angle, vertical	178°	<b>Computer system</b>	
Display number of colours	1.07 billion colours	Computer system *	✓
Panel life	30000 h	Internal memory	8 GB
Native refresh rate	60 Hz	Operating system installed	WebOS
Haze rate	1%	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Display width	1678 mm
HDMI ports quantity *	3	Display depth	59.9 mm
USB port *	✓	Display height	964 mm
USB ports quantity	2	Display weight	31.4 kg
USB version	2.0	Width	1678 mm
Ethernet LAN *	✓	Depth	59.9 mm
Ethernet LAN (RJ-45) ports	1	Height	964 mm
Wi-Fi *	✓	Weight	31.4 kg
Audio (L/R) out	1	<b>Packaging data</b>	
RS-232C	✓	Package width	1820 mm
<b>Audio</b>		Package depth	200 mm
Built-in speaker(s) *	✓	Package height	1115 mm
<b>Design</b>		Package weight	40.3 kg
Product design *	Digital signage flat panel	<b>Packaging content</b>	
Placement supported *	Indoor	Remote control included	✓
Orientation	Horizontal/Vertical	Batteries included	✓
Product colour *	Blue	Cables included	AC
VESA mounting *	✓		

Design		Operational conditions	
Panel mounting interface	400 x 400 mm	Operating temperature (T-T)	0 - 40 °C
Bezel width (bottom)	1.39 cm	Operating relative humidity (H-H)	10 - 80%
Bezel width (side)	1.39 cm	Logistics data	
Bezel width (top)	1.39 cm	Harmonized System (HS) code	85285210
Performance		Features	
Purpose *	Universal	Heat dissipation (max)	751 BTU/h
On Screen Display (OSD)	✓	Other features	
On Screen Display (OSD) languages	Arabic, Traditional Chinese, Czech, Danish, Dutch, English, Finnish, French, Japanese, Norwegian, Portuguese, Russian, Swedish, Turkish	Plug and Play	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAR-2025. Prints or copies of Information are only valid on the printed Publication date