



**Vertiv MG01X4W1-42IZ63-3PS6B2A10-S unità di distribuzione dell'energia (PDU) 42 presa(e) AC Nero**

**Marchio :** Vertiv

**Codice prodotto:** GI10011

**Nome del prodotto :** MG01X4W1-42IZ63-3PS6B2A10-S

Vertiv MG01X4W1-42IZ63-3PS6B2A10-S. Tipi di PDU: Basic, Montaggio: Verticale, Colore del prodotto: Nero. Quantità prese AC: 42 presa(e) AC, Tipo di uscita AC: Accoppiatore C13, Presa di corrente: IEC 60309. Lunghezza cavo: 3 m. Voltaggio nominale di entrata: 200 - 240 V, Corrente massima: 32 A, Frequenza di ingresso AC: 50 - 60 Hz. Certificati di conformità: RoHS

| Design                          |                  | Gestione energetica                           |               |
|---------------------------------|------------------|-----------------------------------------------|---------------|
| Tipi di PDU *                   | Basic            | Frequenza di ingresso AC                      | 50 - 60 Hz    |
| Montaggio                       | Verticale        | Corrente massima *                            | 32 A          |
| Colore del prodotto             | Nero             | Funzionalità di protezione dell'alimentazione | Sovracorrente |
| Interruttore On/Off             | ✓                | Portata termica nominale                      | 7300 W        |
| Connettività                    |                  | Certificati di sicurezza                      |               |
| Quantità prese AC *             | 42 presa(e) AC   | Certificati di conformità                     | RoHS          |
| Presa di corrente               | IEC 60309        | Dimensioni e peso                             |               |
| Tipo di uscita AC *             | Accoppiatore C13 | Larghezza                                     | 51 mm         |
| Caratteristiche                 |                  | Profondità                                    | 51 mm         |
| Lunghezza cavo                  | 3 m              | Altezza                                       | 1778 mm       |
| Gestione energetica             |                  | Peso                                          | 7,26 kg       |
| Voltaggio nominale di entrata * | 200 - 240 V      | Contenuto dell'imballo                        |               |
|                                 |                  | Manuale dell'utente                           | ✓             |



4061471341364

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.