



Vertiv Geist Monitored Outlet Level EC unità di distribuzione dell'energia (PDU) 48 presa(e) AC 0U Nero

Marchio : Vertiv  
Codice prodotto: GR30005L  
Nome del prodotto : Geist Monitored Outlet Level EC

Vertiv Geist Monitored Outlet Level EC. Tipi di PDU: Monitorato, Capacità di rack: 0U, Tipo: Trifase. Quantità prese AC: 48 presa(e) AC, Tipo di uscita AC: Accoppiatore C13, Accoppiatore C19, Presa di corrente: IEC 60309. Lunghezza cavo: 3 m. Monitoraggio: Corrente, Potenza, Tension, Protocolli di rete supportati: DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+. Voltaggio nominale di entrata: 200-240/346-415 V, Frequenza di ingresso AC: 50 - 60 Hz, Voltaggio di uscita: 230 V

| Design                      |                                    | Caratteristiche di gestione        |                                                                                                      |
|-----------------------------|------------------------------------|------------------------------------|------------------------------------------------------------------------------------------------------|
| Tipi di PDU *               | Monitorato                         | Protocolli di rete supportati      | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+ |
| Tipo                        | Trifase                            |                                    |                                                                                                      |
| Capacità di rack *          | 0U                                 |                                    |                                                                                                      |
| Montaggio                   | Verticale                          |                                    |                                                                                                      |
| Colore del prodotto         | Nero                               |                                    |                                                                                                      |
| Tipologia display           | LED                                |                                    |                                                                                                      |
| Connettività                |                                    | Gestione energetica                |                                                                                                      |
| Quantità prese AC *         | 48 presa(e) AC                     | Voltaggio nominale di entrata *    | 200-240/346-415 V                                                                                    |
| Presa di corrente           | IEC 60309                          | Frequenza di ingresso AC           | 50 - 60 Hz                                                                                           |
| Tipo di uscita AC *         | Accoppiatore C13, Accoppiatore C19 | Voltaggio di uscita                | 230 V                                                                                                |
|                             |                                    | Massimo ingresso corrente per fase | 16 A                                                                                                 |
|                             |                                    | Portata termica nominale           | 11000 W                                                                                              |
| Caratteristiche             |                                    | Certificati di sicurezza           |                                                                                                      |
| Tasto reset                 | ✓                                  | Certificati di conformità          | RoHS                                                                                                 |
|                             |                                    | Dimensioni e peso                  |                                                                                                      |
| Indicatori LED              | ✓                                  | Larghezza                          | 1778 mm                                                                                              |
| Lunghezza cavo              | 3 m                                | Profondità                         | 94 mm                                                                                                |
|                             |                                    | Altezza                            | 66 mm                                                                                                |
| Caratteristiche di gestione |                                    | Dati su imballaggio                |                                                                                                      |
| Monitoraggio                | Corrente, Potenza, Tension         | Peso dell'imballo                  | 8,16 kg                                                                                              |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.