

# Vertiv Geist GS30009L unità di distribuzione dell'energia (PDU) 12 presa(e) AC 0U Nero



**Marchio :** Vertiv **Codice prodotto:** GS30009L

**Nome del prodotto :** Geist GS30009L

Vertiv Geist GS30009L. Tipi di PDU: Gestito, Monitorato, Commutate, Capacità di rack: 0U, Montaggio: Verticale. Quantità prese AC: 12 presa(e) AC, Tipo di uscita AC: Accoppiatore C13, Accoppiatore C19, Presa di corrente: IEC 60309. Lunghezza cavo: 3 m. Monitoraggio: Corrente, Potenza, Tension, Protocolli di rete supportati: DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+. Voltaggio nominale di entrata: 200-240 V, Corrente massima: 16 A, Frequenza di ingresso AC: 50 - 60 Hz

| Design                              |                                    | Caratteristiche di gestione     |                                                                                                      |
|-------------------------------------|------------------------------------|---------------------------------|------------------------------------------------------------------------------------------------------|
| Tipi di PDU *                       | Gestito, Monitorato, Commutate     | Monitoraggio                    | Corrente, Potenza, Tension                                                                           |
| Capacità di rack *                  | 0U                                 |                                 | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+ |
| Montaggio                           | Verticale                          | Protocolli di rete supportati   |                                                                                                      |
| Colore del prodotto                 | Nero                               |                                 |                                                                                                      |
| Tipologia display                   | LED                                |                                 |                                                                                                      |
| Connettività                        |                                    | Gestione energetica             |                                                                                                      |
| Quantità prese AC *                 | 12 presa(e) AC                     | Voltaggio nominale di entrata * | 200-240 V                                                                                            |
| Presa di corrente                   | IEC 60309                          | Frequenza di ingresso AC        | 50 - 60 Hz                                                                                           |
| Tipo di uscita AC *                 | Accoppiatore C13, Accoppiatore C19 | Corrente massima *              | 16 A                                                                                                 |
| Porte seriali                       | 2                                  | Voltaggio di output nominale    | 230 V                                                                                                |
| Quantità porte Ethernet LAN (RJ-45) | 2                                  | Portata termica nominale        | 3600 W                                                                                               |
| Caratteristiche                     |                                    | Certificati di sicurezza        |                                                                                                      |
| Catena Daisy                        | ✓                                  | Certificati di conformità       | RoHS                                                                                                 |
| Tasto reset                         | ✓                                  | Certificazione                  | CE, EN55032, EN55024, IEC 60950-1, RCM                                                               |
| Indicatori LED                      | ✓                                  |                                 |                                                                                                      |
| Lunghezza cavo                      | 3 m                                | Dimensioni e peso               |                                                                                                      |
|                                     |                                    | Larghezza                       | 864 mm                                                                                               |
|                                     |                                    | Profondità                      | 66 mm                                                                                                |
|                                     |                                    | Altezza                         | 51 mm                                                                                                |
|                                     |                                    | Peso                            | 8,16 kg                                                                                              |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.