


LG 22XE1J-B Pannello piatto per segnaletica digitale 55,9 cm (22") Wi-Fi 1500 cd/m² Full HD Nero WebOS 24/7

Marchio: LG Codice prodotto: 22XE1J-B.AEU

Nome del prodotto: 22XE1J-B







Display		Performance	
Panel type LED backlighting type Display diagonal * Display resolution *	AHVA Edge-LED 55.9 cm (22") 1920 x 1080 pixels	Operating hours (hours/days) HDCP International Protection (IP) code HDCP version	24/7 ✓ IP56 1.4
Display brightness *	1500 cd/m ²	Power	
HD type * Touchscreen * Native aspect ratio Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical	Full HD X 16:9 1000:1 800000:1 178° 178°	Power consumption (typical) * Power consumption (standby) * Power consumption (off) AC input voltage AC input frequency Heat dissipation	85 W 0.5 W 0.5 W 100-240 V 50-60 Hz 290 BTU/h
Display number of colours	16.7 million colours	Computer system	
Number of displays 1 Colour saturation 72% Rated lifetime 50000 h Native refresh rate 60 Hz	72% 50000 h 60 Hz	Computer system * Built-in processor * Internal memory Operating system installed	X X 16 GB WebOS
Haze rate	25% NTSC	Weight & dimensions	
Ports & interfaces HDMI ports quantity * 1 DVI port * NTSC NTSC 1 X	1	Display width Display depth Display height Display weight	557.3 mm 66 mm 319.8 mm 8.7 kg
USB port *	✓	Packaging data	-
USB ports quantity USB version USB connector type Ethernet LAN *	1 2.0 USB Type-A ✓	Package width Package depth Package height Package weight	632 mm 187 mm 394 mm 10 kg
Ethernet LAN (RJ-45) ports Wi-Fi *	1	Packaging content	
Audio (L/R) out	1	Stand included	✓
Audio		Stand colour	Black/Silver
Built-in speaker(s) *	×	Remote control included Batteries included Cables included	✓ ✓ AC, RS-232

Design		Packaging content	
Product design *	Digital signage flat panel Outdoor	Tilt adjustment	✓
Placement supported *		Operational conditions	
Orientation Product colour * Screen shape	Horizontal/Vertical Black Flat	Operating temperature (T-T) Operating relative humidity (H-H)	-30 - 0 °C 50 - 100%
VESA mounting *	✓	Features	
Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top)	100 x 100 mm 24 cm 24 cm 3.83 cm	Base colour Suitable for outdoor use Wall mountable Heat dissipation (max)	Black ✓ ✓ 393 BTU/h
Anti-glare screen	✓	Technical details	
Performance Purpose * Wi-Fi Direct Browsing On Screen Display (OSD) Number of OSD languages On Screen Display (OSD) languages	Japanese, Korean, Norwegian, Portuguese, Russian, Swedish, Turkish	Special features	Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail over, Background Image (Booting Logo Image, No Signal Image), Sync Mode (Local Network Sync), Video Tag (4, Max One HDMI input), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Setting Data Cloning, SNMP, ISM Method, Status Mailing, Control Manager, Power (Smart Energy Saving, PM mode, Wake on LAN, Network Ready), Beacon, HDMI-CEC, SI Server Setting , webRTC, Pro:Idiom
Ambient light sensor	✓	Sustainability certificates	ErP
		Compliance certificates	CE, Federal Communications Commission (FCC)

