

Allied Telesis AT-2911GP/SFP-001 Interno Ethernet / Fiber 1000 Mbit/s

Marchio : Allied Telesis

Codice prodotto: 990-003519-001

Nome del prodotto : AT-2911GP/SFP-001

Allied Telesis AT-2911GP/SFP-001. Interno. Tecnologia di connessione: Cablato, Interfaccia host: PCI Express, Interfaccia: Ethernet / Fiber. Velocità massima di trasferimento dati: 1000 Mbit/s. Colore del prodotto: Verde, Argento

Connettività		Design	
Tecnologia di connessione *	Cablato	Colore del prodotto	Verde, Argento
Interfaccia host *	PCI Express	Interno *	✓
Interfaccia *	Ethernet / Fiber	Indicatori LED	✓
Quantità porte Ethernet LAN (RJ-45)	1	Requisiti di sistema	
Connettore a fibra ottica	SFP		
Collegamento in rete		Sistema operativo Windows supportato Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
Velocità massima di trasferimento dati *	1000 Mbit/s		
Standard di rete *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.2, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z		
Collegamento ethernet LAN	✓		
Tipo di interfaccia Ethernet	Gigabit Ethernet		
Velocità trasferimento Ethernet LAN	10,100,1000 Mbit/s		
Tecnologia di cablaggio	10/100/1000BaseT(X)		
		Condizioni ambientali	
		Intervallo temperatura di funzionamento	0 - 40 °C
		Intervallo di temperatura	-25 - 70 °C
		Range di umidità di funzionamento	5 - 90%
		Dimensioni e peso	
		Larghezza	88 mm
		Altezza	69 mm
		Peso	68 g



0767035197005



767035197005

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.