



**QNAP QSW-M3216R-8S8T switch di rete Gestito L2/L3 10G Ethernet (100/1000/10000) 1U Nero**



**Marchio :** QNAP

**Codice prodotto:** QSW-M3216R-8S8T

**Nome del prodotto :** QSW-M3216R-8S8T

QNAP QSW-M3216R-8S8T. Tipo interruttore: Gestito, Livello del commutatore: L2/L3. Tipo di porte RJ-45: 10G Ethernet (100/1000/10000), Quantità di porte RJ-45: 8, Quantità di moduli SFP+ installati: 8, Console port: RJ-45. Dimensioni tavola MAC: 16000 voci, Capacità di commutazione: 320 Gbit/s. Standard di rete: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Montaggio rack, Fattore di forma: 1U



| Caratteristiche di gestione          |                                                                                            | Sicurezza                               |             |
|--------------------------------------|--------------------------------------------------------------------------------------------|-----------------------------------------|-------------|
| Tipo interruttore *                  | Gestito                                                                                    | Lista di controllo accesso (ACL)        | ✓           |
| Livello del commutatore              | L2/L3                                                                                      | Design                                  |             |
| Connettività                         |                                                                                            | Montaggio rack *                        | ✓           |
| Quantità di porte RJ-45 *            | 8                                                                                          | Fattore di forma                        | 1U          |
| Tipo di porte RJ-45 *                | 10G Ethernet (100/1000/10000)                                                              | Colore del prodotto                     | Nero        |
| Quantità di moduli SFP+ installati * | 8                                                                                          | Gestione energetica                     |             |
| Console port                         | RJ-45                                                                                      | Alimentazione *                         | AC          |
| Collegamento in rete                 |                                                                                            | Tensione di ingresso AC                 | 100 - 240 V |
| Standard di rete *                   | IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Frequenza di ingresso AC                | 50/60 Hz    |
| Supporto 10G *                       | ✓                                                                                          | Consumo energetico (max)                | 48,632 W    |
| Supporto controllo flusso            | ✓                                                                                          | Condizioni ambientali                   |             |
| Trasmissione dati                    |                                                                                            | Intervallo temperatura di funzionamento | 0 - 40 °C   |
| Capacità di commutazione *           | 320 Gbit/s                                                                                 | Range di umidità di funzionamento       | 5 - 95%     |
| Capacità di trasmissione             | 160 Gbit/s                                                                                 | Dimensioni e peso                       |             |
| Dimensioni tavola MAC *              | 16000 voci                                                                                 | Larghezza                               | 207 mm      |
| Supporto Jumbo Frames                | ✓                                                                                          | Profondità                              | 199,5 mm    |
| Frame Jumbo                          | 9000                                                                                       | Altezza                                 | 43,3 mm     |
|                                      |                                                                                            | Peso                                    | 1,52 kg     |



4711103084311

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.