



APC SYA16K16I gruppo di continuità (UPS) 16 kVA 11200 W

Marchio : APC

Codice prodotto: SYA16K16I

Nome del prodotto : SYA16K16I

APC SYA16K16I. Potenza in uscita: 16 kVA, Potenza in uscita: 11200 W. Tempo di salvataggio minimo a pieno carico: 7,5 min, Tempo di salvataggio minimo a mezzo carico: 20,3 min, Cartuccia batterie sostitutiva: SYBT5. Peso: 308 kg. Tipo batteria: Maintenance-free sealed Lead-Acid battery with suspended electrolyte: leakproof, Interfaccia: DB-9 RS-232, Smart-Slot, Connessioni output: (1) Hard Wire 3-wire (H N + G)



| Caratteristiche                            |             | Condizioni ambientali                    |                                                                                       |
|--------------------------------------------|-------------|------------------------------------------|---------------------------------------------------------------------------------------|
| Potenza in uscita *                        | 16 kVA      | Altitudine di funzionamento              | 0 - 3000 m                                                                            |
| Potenza in uscita *                        | 11200 W     | Dimensioni e peso                        |                                                                                       |
| Spegnimento di emergenza (EPO)             | ✓           | Peso                                     | 308 kg                                                                                |
| Batteria                                   |             | Dati logistici                           |                                                                                       |
| Tempo di salvataggio minimo a pieno carico | 7,5 min     | Codice del Sistema Armonizzato (SA)      | 85078000                                                                              |
| Tempo di salvataggio minimo a mezzo carico | 20,3 min    | Impronta di carbonio totale (kg of CO2e) | 53926,34                                                                              |
| Cartuccia batterie sostitutiva             | SYBT5       | Altre caratteristiche                    |                                                                                       |
| Condizioni ambientali                      |             | Porte I/O                                | Available Smart Slot Interface<br>Quantity - 1 Pre-Installed SmartSlot Cards - AP9619 |
| Intervallo temperatura di funzionamento    | 0 - 40 °C   | Tipo batteria                            | Maintenance-free sealed Lead-Acid battery with suspended electrolyte: leakproof       |
| Intervallo di temperatura                  | -15 - 45 °C | Interfaccia                              | DB-9 RS-232, Smart-Slot                                                               |
| Range di umidità di funzionamento          | 0 - 95%     | Connessioni output                       | (1) Hard Wire 3-wire (H N + G)                                                        |
| Umidità                                    | 0 - 95%     | Tipo connessione ingresso                | Hard Wire 3 wire (1PH+N+G), Hard Wire 5-wire (3PH + N + G)                            |
|                                            |             | Dimensioni (LxPxA)                       | 480 x 730 x 940 mm                                                                    |
|                                            |             | Voltaggio di output nominale             | 230 V                                                                                 |
|                                            |             | Voltaggio in uscita                      | Configurable for 220: 230 or 240 nominal output voltage                               |



0200000925482



200000925482



8592978116927



5054444280202



3606485318745

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.